DampMaster Plus



Professional material moisture measuring device for wood and building materials, featuring a Digital Connection interface and a clear display showing all relevant readings simultaneously

This professional material moisture measuring device determines the moisture content of 111 wood types and 42 building materials by mass %. In addition, the CM mode is available for 12 building materials, to evaluate the moisture content in CM %, comparable to the calcium carbide method. High measuring accuracy can be achieved thanks to material-specific measurements. The clear display simultaneously shows all key data, including material moisture, maximum reading, reference value and ambient temperature. The wet/dry indicator has 12 coloured LEDs and provides immediate information on the degree of moisture and/or dryness of the material. The universal index mode quickly localises moisture using comparative measurements. Measurement data can be easily transferred to a smartphone via the Digital Connection interface.

- Fast and precise measurement of wood and building moisture
- High measurement accuracy thanks to material-specific moisture analysis of 111 wood types and 42 building materials as mass in %
- CM mode: Evaluation of 12 building materials, including cement screed and anhydrite screed, in CM %, comparable to the calcium carbide method
- Clear display showing material moisture, maximum value, reference value and ambient temperature simultaneously











DIGITAL CONNECTION · Laserliner · 4x AAA

TECHNICAL DATA	
Measured Variable	Moisture content of material (resistive) Ambient temperature
Mode	Building materials (42 materials) CM Mode (12 materials) Wood (3 groups) Index Self-test function
Measuring Range Wood	Wood group A: 4.6% … 91.6% Wood group B: 6.1% … 103.6% Wood group C: 3.0% … 79.2%
Accuracy (Absolute) Wood	± 1% (5% … 30%) ± 2% (<5% and >30%)
Measuring Range Building Materials	Anhydrite screed (AE, AFE): 0% … 29.5% Concrete C12/15: 0.7% … 3.3% Concrete C20/C25: 1.1% … 3.9% Concrete C30/C37: 1.4% … 3.7% Gypsum plaster: 0.1% … 38% Limestone, bulk density 1.9: 0.8% … 12.7% Cellular concrete (Hebel): 2.2% ... 171.2% Cement screed without additive: 1.0% … 4.5%
Accuracy (Absolute) Building Materials	± 0.15%

SCOPE OF DELIVERY





Item No. 082.328A	GTIN (EAN) 4021563734429	SU 1

UMAREX GmbH & Co. KG • Laserliner • Gut Nierhof 2 • 59757 Arnsberg • Germany • Tel. +49 2932 9004-0 • info@laserliner.com • www.laserliner.com