


WL 380



- Effective illumination by 280 lumens spotlight and 380 lumens floodlight
- The floodlight has three light levels (low/medium/high) and two spotlight levels (high/low) to suit all requirements
- Versatile attachment by hook, magnet or swivel stand
- Optimum positioning by tilting through up to 180°
- Compact design makes it easy to carry in a pocket
- Easy to read battery charge status display
- Integral lithium-ion rechargeable battery
- Rechargeable via USB-C cable

This practical LED work light offers a spotlight with two light levels (high/low) and a floodlight with three light levels (low/medium/high). The product has a multi-function bracket for optimum attachment and positioning. It can be tilted through 180°, has a hook for hanging, and magnets for fixing to metal surfaces. When working on metal constructions or vehicles, users' hands are free at all times allowing them to concentrate fully on the job in hand. An easy to read display provides information on the charge status of the integral lithium-ion battery. A USB-C cable is included in the delivery to charge the battery.

TECHNICAL DATA	
Luminosity Low	12 lm
Luminosity High	380 lm
Lightning Rage (Max.)	100 m
Lighting Time Low	approx. 102 hours
Lighting Time High	approx. 6 hours
CRI Value	> 80
LED Chip	High power LED
Photobiological Safety	Risk group 1 (DIN EN 62471)
Protection Class	IP X5
Ports	USB type C
Power Supply	Li-ion battery pack 3.7V / 2.6Ah
Dimensions (W x H x D)	51 mm x 123 mm x 34 mm
Weight	180 g (incl. batteries)



Item No.	GTIN (EAN)	SU
602.206A	4021563724642	5

SCOPE OF DELIVERY



WL 380, USB-C-cable